

# Chapter 16-662 WAC

## WEIGHTS AND MEASURES—NATIONAL HANDBOOKS AND RETAIL SALE OF MOTOR FUEL

### WAC

16-662-100	Purpose.
16-662-105	Standards adopted by the Washington state department of agriculture (WSDA).
16-662-110	Modifications to NIST Handbook 44.
16-662-115	Modifications to NIST Handbook 130.
16-662-120	Inspections of the net contents of packaged goods under NIST Handbook 133.
16-662-125	Enforcement actions for price verification inspections under NIST Handbook 130.
16-662-140	Retail sales of motor fuels.
16-662-145	Posting of motor fuel prices—Cash and credit sales.

**Reviser's note:** NBS Handbook 44, Fourth Edition, filed June 18, 1973, Order 1318 entitled "Specifications, Tolerances and Other Technical Requirements for Commercial Weighing and Measuring Devices" and 1975 replacement sheets for NBS Handbook 44 - fourth edition, filed August 18, 1976. By authority of RCW 34.05.210(4), this edition has been omitted from publication in the Washington Administrative Code. Copies may be purchased from the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.

### DISPOSITION OF SECTIONS FORMERLY CODIFIED IN THIS CHAPTER

16-662-001,	16-662-002, 16-662-003, 16-662-010, 16-662-020, and 16-662-030; provisions of National Bureau of Standards Handbook 44, 2nd edition, as set forth in RCW 19.93.060 have been superseded in total by the 3rd edition, as amended in 1966. [Order 1035, filed 11/14/66, effective 12/15/66 and Order 1072, filed 11/27/67, effective 1/1/68.] Handbook 44 may be purchased from the Superintendent of Documents, U.S. Government Printing Office, Washington 25, D.C.
16-662-040	Promulgation—Weights and measures regulation adopting National Bureau of Standards Handbook 44, 3rd edition. [Order 1134, § 16-662-040, filed 12/29/69, effective 2/1/70; Order 1035, Regulation 1, filed 11/14/66, effective 12/15/66.] Repealed by Order 1318, filed 6/18/73, effective 8/1/73. Later promulgation, see WAC 16-662-070.
16-662-050	Promulgation—Weights and measures regulation adopting amendments to National Bureau of Standards Handbook 44, 3rd edition. [Order 1072, Regulation 1, filed 11/27/67, effective 1/1/68.] Repealed by Order 1134, filed 12/29/69, effective 2/1/70. See later enactment WAC 16-662-040.
16-662-060	Promulgation—Weights and measures regulations adopting National Bureau of Standards Handbook 44, 4th edition as amended in 1972. [Order 1318, § 16-662-060, filed 6/18/73, effective 8/1/73.] Repealed by Order 1480, filed 8/18/76. Later promulgation, see WAC 16-662-071.
16-662-070	Promulgation. [Order 1480, § 16-662-070, filed 8/18/76. Formerly WAC 16-662-040.] Repealed by WSR 97-12-075, filed 6/4/97, effective 7/5/97. Statutory Authority: Chapter 19.94 RCW.
16-662-071	Replacement of amendments. [Order 1480, § 16-662-071, filed 8/18/76. Formerly WAC 16-662-060.] Repealed by WSR 97-12-075, filed 6/4/97, effective 7/5/97. Statutory Authority: Chapter 19.94 RCW.

**WAC 16-662-100 Purpose.** (1) This chapter establishes requirements for the state of Washington that are reasonably consistent with the uniform rules adopted by the National Conference on Weights and Measures and published by the National Institute of Standards and Technology (NIST). This

(1/11/13)

chapter also establishes requirements for the retail sale and advertising of motor fuel.

(2) This chapter applies specifically to the:

(a) Uniform specifications, tolerances and other technical requirements for weighing and measuring devices addressed in *NIST Handbook 44*;

(b) Uniform procedures for checking the net contents of packaged goods addressed in *NIST Handbook 133*;

(c) Uniform packaging and labeling regulation addressed in *NIST Handbook 130*;

(d) Uniform regulation for the method of sale of commodities addressed in *NIST Handbook 130*;

(e) Uniform examination procedure for price verification addressed in *NIST Handbook 130*;

(f) Engine fuels, petroleum products, and automotive lubricants regulation addressed in *NIST Handbook 130*;

(g) Specifications and tolerances for reference standards and field standard weights and measures addressed in the *NIST Handbook 105* series; and

(h) Requirements for the retail sale and advertising of motor fuel.

(3)(a) *NIST Handbook 44*, *NIST Handbook 130*, *NIST Handbook 133*, and *NIST Handbooks 105* may be purchased from the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402 and are available on the National Institute of Standards and Technology web site at <http://www.nist.gov/pml/wmd/pubs/handbooks.cfm>.

(b) For information regarding the contents and application of these publications, contact the weights and measures program at the Washington State Department of Agriculture, P.O. Box 42560, Olympia, Washington 98504-2560, telephone number 360-902-1857, or e-mail [wts&measures@agr.wa.gov](mailto:wts&measures@agr.wa.gov).

[Statutory Authority: RCW 19.94.190, 19.112.020, 19.112.140 and chapter 34.05 RCW. WSR 13-03-054, § 16-662-100, filed 1/11/13, effective 2/11/13. Statutory Authority: Chapters 19.94, 19.112, and 34.05 RCW. WSR 12-02-021, § 16-662-100, filed 12/28/11, effective 1/28/12; WSR 09-19-007, § 16-662-100, filed 9/3/09, effective 10/4/09. Statutory Authority: Chapters 19.112 and 34.05 RCW. WSR 07-05-083, § 16-662-100, filed 2/21/07, effective 3/24/07. Statutory Authority: Chapters 19.94 and 34.05 RCW. WSR 05-10-088, § 16-662-100, filed 5/4/05, effective 6/4/05; WSR 03-08-017, § 16-662-100, filed 3/25/03, effective 4/25/03. Statutory Authority: Chapter 19.94 RCW. WSR 97-12-075, § 16-662-100, filed 6/4/97, effective 7/5/97.]

**WAC 16-662-105 Standards adopted by the Washington state department of agriculture (WSDA).** Except as otherwise modified in this chapter, the WSDA adopts the following national standards:

[Ch. 16-662 WAC p. 1]

National standard for:	Contained in the:
(1) The specifications, tolerances, and other technical requirements for the design, manufacture, installation, performance test, and use of weighing and measuring equipment	2013 Edition of <i>NIST Handbook 44 - Specifications, Tolerances, and Other Technical Requirements for Weighing and Measuring Devices</i>
(2) The procedures for checking the accuracy of the net contents of packaged goods	2013 Edition of <i>NIST Handbook 133 - Checking the Net Contents of Packaged Goods</i>
(3) The requirements for packaging and labeling, method of sale of commodities, examination procedures for price verification, and engine fuels, petroleum products and automotive lubricants	2013 Edition of <i>NIST Handbook 130 - Uniform Laws and Regulations in the areas of legal metrology and engine fuel quality</i> . Specifically:
(a) Weights and measures requirements for all food and nonfood commodities in package form	<i>Uniform Packaging and Labeling Regulation</i> as adopted by the National Conference on Weights and Measures and published in <i>NIST Handbook 130</i> , 2013 Edition.
(b) Weights and measures requirements for the method of sale of food and nonfood commodities	<i>Uniform Regulation for the Method of Sale of Commodities</i> as adopted by the National Conference on Weights and Measures and published in <i>NIST Handbook 130</i> , 2013 Edition.
(c) Weights and measures requirements for price verification	<i>Examination Procedure for Price Verification</i> as adopted by the National Conference on Weights and Measures and published in <i>NIST Handbook 130</i> , 2013 Edition.
(d) Definitions; standard fuel specifications; classification and method of sale of petroleum products; retail storage tanks and dispenser filters; condemned product; product registration; and test methods and reproducibility limits	<i>Uniform Engine Fuels and Automotive Lubricants Regulation</i> as adopted by the National Conference on Weights and Measures and published in <i>NIST Handbook 130</i> , 2013 Edition.
(4) Specifications and tolerances for reference standards and field standard weights and measures	<i>NIST Handbook 105-1, Specifications and Tolerances for Field Standard Weights (NIST Class F) - 1990</i> ;
	<i>NIST Handbook 105-2, Specifications and Tolerances for Field Standard Measuring Flasks - 1996</i> ;

National standard for:	Contained in the:
	<i>NIST Handbook 105-3, Specifications and Tolerances for Graduated Neck Type Volumetric Field Standards - 2010</i> ;
	<i>NIST Handbook 105-4, Specifications and Tolerances for Liquefied Petroleum Gas and Anhydrous Ammonia Liquid Volumetric Provers - 2010</i> ;
	<i>NIST Handbook 105-5, Specifications and Tolerances for Field Standard Stopwatches - 1997</i> ;
	<i>NIST Handbook 105-6, Specifications and Tolerances for Thermometers - 1997</i> ;
	<i>NIST Handbook 105-7, Specifications and Tolerances for Dynamic Small Volume Provers - 1997</i> ;
	<i>NIST Handbook 105-8, Specifications and Tolerances for Field Standard Weight Carts - 2003</i> .

[Statutory Authority: RCW 19.94.190, 19.112.020, 19.112.140 and chapter 34.05 RCW. WSR 13-03-054, § 16-662-105, filed 1/11/13, effective 2/11/13; WSR 12-08-041, § 16-662-105, filed 3/30/12, effective 4/30/12. Statutory Authority: Chapters 19.94, 19.112, and 34.05 RCW. WSR 12-02-021, § 16-662-105, filed 12/28/11, effective 1/28/12. Statutory Authority: Chapters 19.94, 19.112, 34.05 RCW, and 2010 c 96. WSR 10-18-088, § 16-662-105, filed 9/1/10, effective 10/2/10. Statutory Authority: Chapters 19.94, 19.112, and 34.05 RCW. WSR 09-19-007, § 16-662-105, filed 9/3/09, effective 10/4/09. Statutory Authority: Chapters 19.94 and 34.05 RCW. WSR 08-05-007, § 16-662-105, filed 2/7/08, effective 3/9/08. Statutory Authority: Chapters 19.112 and 34.05 RCW. WSR 07-05-083, § 16-662-105, filed 2/21/07, effective 3/24/07. Statutory Authority: Chapters 19.94 and 34.05 RCW. WSR 07-01-115A, § 16-662-105, filed 12/20/06, effective 1/20/07; WSR 06-08-102, § 16-662-105, filed 4/5/06, effective 5/6/06; WSR 05-10-088, § 16-662-105, filed 5/4/05, effective 6/4/05; WSR 04-12-025, § 16-662-105, filed 5/26/04, effective 6/26/04; WSR 03-08-017, § 16-662-105, filed 3/25/03, effective 4/25/03. Statutory Authority: Chapter 19.94 RCW. WSR 02-12-029, § 16-662-105, filed 5/29/02, effective 6/29/02. Statutory Authority: RCW 19.94.195. WSR 01-16-005, § 16-662-105, filed 7/19/01, effective 8/19/01; WSR 00-14-005, § 16-662-105, filed 6/23/00, effective 7/24/00; WSR 99-07-056, § 16-662-105, filed 3/16/99, effective 4/16/99; WSR 98-13-072, § 16-662-105, filed 6/15/98, effective 7/16/98. Statutory Authority: Chapter 19.94 RCW. WSR 97-12-075, § 16-662-105, filed 6/4/97, effective 7/5/97.]

**WAC 16-662-110 Modifications to NIST Handbook 44.** The WSDA adopts the following modifications to *NIST Handbook 44*, which is identified in WAC 16-662-105(1):

Modified Section:	Modification:
<i>NIST Handbook 44</i> , 2013 Edition, Section 3-30, Liquid-Measuring Devices	The standards and specifications in <i>NIST Handbook 44</i> , 2012 Edition Section 3-30. Liquid-Measuring Devices will be used instead of the 2013 edition.

Modified Section:	Modification:
<i>NIST Handbook 44</i> , 2013 Edition, General Code: Section G-UR.4.1. Maintenance of Equipment	In the last sentence of G-UR.4.1., Maintenance of Equipment, change the words "device user" to "device owner or operator." As a result of this modification, the last sentence of G-UR.4.1. will read:  "Equipment in service at a single place of business found to be in error predominantly in a direction favorable to the device owner or operator (see also Introduction, Section Q) shall not be considered "maintained in a proper operating condition.""
<i>NIST Handbook 44</i> , 2012 Edition, Liquid-Measuring Devices: Section S.1.6.4.1. Unit Price	At the end of the first sentence of S.1.6.4.1.(b), Unit Price, add the words "or after prepayment for the product but prior to its delivery." As a result of this modification, the sentence will read: "Whenever a grade, brand, blend, or mixture is offered for sale from a device at more than one unit price, then all of the unit prices at which that product is offered for sale shall be displayed or shall be capable of being displayed on the dispenser using controls available to the customer prior to the delivery of the product or after prepayment for the product but prior to its delivery."

[Statutory Authority: RCW 19.94.190, 19.112.020, 19.112.140 and chapter 34.05 RCW. WSR 13-03-054, § 16-662-110, filed 1/11/13, effective 2/11/13. Statutory Authority: Chapters 19.94, 19.112, and 34.05 RCW. WSR 12-02-021, § 16-662-110, filed 12/28/11, effective 1/28/12. Statutory Authority: Chapters 19.94, 19.112, 34.05 RCW, and 2010 c 96. WSR 10-18-088, § 16-662-110, filed 9/1/10, effective 10/2/10. Statutory Authority: Chapters 19.94, 19.112, and 34.05 RCW. WSR 09-19-007, § 16-662-110, filed 9/3/09, effective 10/4/09. Statutory Authority: Chapters 19.94 and 34.05 RCW. WSR 07-01-115A, § 16-662-110, filed 12/20/06, effective 1/20/07; WSR 05-10-088, § 16-662-110, filed 5/4/05, effective 6/4/05; WSR 03-08-017, § 16-662-110, filed 3/25/03, effective 4/25/03. Statutory Authority: RCW 19.94.195. WSR 01-16-005, § 16-662-110, filed 7/19/01, effective 8/19/01; WSR 99-07-056, § 16-662-110, filed 3/16/99, effective 4/16/99. Statutory Authority: Chapter 19.94 RCW. WSR 97-12-075, § 16-662-110, filed 6/4/97, effective 7/5/97.]

**WAC 16-662-115 Modifications to NIST Handbook 130.** The WSDA adopts the following modifications to the listed sections of the *Uniform Regulation for the Method of Sale of Commodities* requirements published in *NIST Handbook 130*, identified in WAC 16-662-105 (3)(b):

Modified Section:	Modification:
(1) Section 2.20.1. Method of Retail Sale	Modify section 2.20.1. Method of Retail Sale. Type of Oxygenate must be Disclosed, to read: "All automotive gasoline or automotive gasoline-oxygenate blends

Modified Section:	Modification:
	kept, offered, or exposed for sale, or sold at retail containing at least 1.5 mass percent oxygen shall be identified as "with" or "containing" (or similar wording) the predominant oxygenate in the engine fuel. For example, the label may read "contains ethanol." The oxygenate contributing the largest mass percent oxygen to the blend shall be considered the predominant oxygenate. Where mixtures of only ethers are present, the retailer may post the predominant oxygenate followed by the phrase "or other ethers." In addition, gasoline-methanol blend fuels containing more than 0.15 mass percent oxygen from methanol shall be identified as "with" or "containing" methanol. This information shall be posted on the upper fifty percent of the dispenser front panel in a position clear and conspicuous from the driver's position in a type at least 12.7 mm (1/2 in.) in height, 1.5 mm (1/16 in.) stroke (width of type). Methanol at one percent or greater, by volume, in gasoline for use as motor vehicle fuel must be labeled with the maximum percentage of methanol contained in the motor vehicle fuel. Ethanol at no less than one percent and no more than ten percent, by volume, must be labeled "Contains up to 10% Ethanol." Ethanol at greater than ten percent by volume must be labeled with the capital letter E followed by the numerical value volume percent denatured ethanol and ending with the word "ethanol." (Example: E85 Ethanol.)"
(2) Section 2.20.2. Documentation for Dispenser Labeling Purposes	Modify section 2.20.2. Documentation for Dispenser Labeling Purposes, to read: "At the time of delivery of the fuel, the retailer shall be provided, on an invoice, bill of lading, shipping paper, or other documentation a declaration of the predominant oxygenate or combination of oxygenates present in concentrations sufficient to yield an oxygen content of at least 1.5 mass percent in the fuel. Where mixtures of only ethers are present, the fuel supplier may

Modified Section:	Modification:
	identify the predominant oxygenate in the fuel (i.e., the oxygenate contributing the largest mass percent oxygen). In addition, any gasoline containing more than 0.15 mass percent oxygen from methanol shall be identified as "with" or "containing" methanol. This documentation is only for dispenser labeling purposes; it is the responsibility of any potential blender to determine the total oxygen content of the engine fuel before blending. When ethanol and/or methanol is blended at one percent or greater, by volume, in gasoline for use as motor vehicle fuel, documentation must include the volumetric percentage of ethanol and/or methanol."
(3) Section 2.23. Animal Bedding	Add a new subsection which reads: "2.23.2. Sawdust, Barkdust, Decorative Wood Particles, and Similar Products. As used in this subsection, "unit" means a standard volume equal to 200 cubic feet. When advertised, offered for sale, or sold within Washington state, quantity representations for sawdust, barkdust, decorative wood particles, and similar loose bulk materials must be in cubic measures or units and fractions thereof."
(4) Section 2.31.2. Labeling of Retail Dispensers	Add a new subsection which reads: "2.31.2.5. Labeling of Retail Dispensers Containing Not More Than 5% Biodiesel. Each retail dispenser of biodiesel or biodiesel blend containing not more than five percent biodiesel must be labeled "May contain up to 5% Biodiesel.""  Add a new subsection which reads: "2.31.2.6. Labeling of Retail Dispensers Containing More Than 5% Biodiesel. Each retail dispenser of biodiesel or biodiesel blend containing more than five percent biodiesel must be labeled with the capital letter B followed by the numerical value representing the volume percentage of biodiesel fuel and ending with either "biodiesel" or "biodiesel blend" (examples: B100 Biodiesel; B60 Biodiesel Blend)."

Modified Section:	Modification:
(5) Section 2.31.4. Exemption	Delete section 2.31.4.

The WSDA adopts the following modifications to the listed sections of the *Uniform Engine Fuels and Automotive Lubricants Regulation* requirements published in *NIST Handbook 130*, identified in WAC 16-662-105 (3)(d):

Modified Section:	Modification:
(1) Section 2.1.2. Gasoline-Ethanol Blends	Modify section 2.1.2. to read: "When gasoline is blended with 1 to 10 volume percent ethanol, the ethanol shall meet the requirements of ASTM D4806 and either:  (a) The base gasoline used for blending with ethanol shall meet the requirements of ASTM D4814; except that the base gasoline shall meet the minimum temperature for a Vapor-Liquid Ratio of 20 for the applicable vapor lock protection class as follows:  (1) Class 1 shall be 60°C (140°F) (2) Class 2 shall be 56°C (133°F) (3) Class 3 shall be 51°C (124°F) (4) Class 4 shall be 47°C (116°F) (5) Class 5 shall be 41°C (105°F)  or  (b) The blend shall meet the requirements of ASTM D4814."  Add a new subsection to read: " 2.1.2.1. Maximum Vapor Pressure. The maximum vapor pressure of a gasoline-ethanol blend shall not exceed ASTM D4814 limits by more than 1.0 psi for:  (a) Only 9 to 10 volume percent ethanol blends from June 1 through September 15.  (b) All blends of 1 to 10 volume percent ethanol from September 16 through May 31."
(2) Section 2.12. Motor Oil	Delete section 2.12.
(3) Section 2.13. Products for Use in Lubricating Manual Transmissions, Gears, or Axles	Delete section 2.13.
(4) Section 2.14. Products for Use in Lubricating Automatic Transmissions	Delete section 2.14.

Modified Section:	Modification:
(5) Section 3.2.6. Method of Retail Sale	<p>Modify section 3.2.6. to read: "Type of Oxygenate must be Disclosed. All automotive gasoline or automotive gasoline-oxygenate blends kept, offered, or exposed for sale, or sold at retail containing at least 1.5 mass percent oxygen shall be identified as "with" or "containing" (or similar wording) the predominant oxygenate in the engine fuel. For example, the label may read "contains ethanol." The oxygenate contributing the largest mass percent oxygen to the blend shall be considered the predominant oxygenate. Where mixtures of only ethers are present, the retailer may post the predominant oxygenate followed by the phrase "or other ethers." In addition, gasoline-methanol blend fuels containing more than 0.15 mass percent oxygen from methanol shall be identified as "with" or "containing" methanol. This information shall be posted on the upper fifty percent of the dispenser front panel in a position clear and conspicuous from the driver's position in a type at least 12.7 mm (1/2 in.) in height, 1.5 mm (1/16 in.) stroke (width of type). Methanol at one percent or greater, by volume, in gasoline for use as motor vehicle fuel must be labeled with the maximum percentage of methanol contained in the motor vehicle fuel. Ethanol at no less than one percent and no more than ten percent, by volume, must be labeled "Contains up to 10% Ethanol." Ethanol at greater than ten percent by volume must be labeled with the capital letter E followed by the numerical value volume percent denatured ethanol and ending with the word "ethanol" (example: E85 Ethanol)."</p>
(6) Section 3.2.7. Documentation for Dispenser Labeling Purposes	<p>Modify section 3.2.7. to read: "The retailer shall be provided, at the time of delivery of the fuel, on an invoice, bill of lading, shipping paper, or other documentation, a declaration of the predominant oxygenate or combination of oxygenates present in concentrations sufficient to yield an oxygen content of at least 1.5 mass percent in the fuel. Where mixtures of only ethers are present, the fuel supplier</p>

Modified Section:	Modification:
	<p>may identify the predominant oxygenate in the fuel (i.e., the oxygenate contributing the largest mass percent oxygen). In addition, any gasoline containing more than 0.15 mass percent oxygen from methanol shall be identified as "with" or "containing" methanol. This documentation is only for dispenser labeling purposes; it is the responsibility of any potential blender to determine the total oxygen content of the engine fuel before blending. When ethanol and/or methanol is blended at one percent or greater, by volume, in gasoline for use as motor vehicle fuel, documentation must include the volumetric percentage of ethanol and/or methanol."</p>
(7) Section 3.8.2. Labeling Requirements	<p>Add a new subsection which reads: "(c) Each retail dispenser of greater than ten percent fuel ethanol by volume must be labeled with the capital letter E followed by the numerical value volume percent denatured ethanol and ending with the word "ethanol" (example: E85 Ethanol)."</p>
(8) Section 3.9.2. Retail Dispenser Labeling	<p>Add a new subsection which reads: "(c) Each retail dispenser of fuel methanol shall be labeled by the capital letter M followed by the numerical value maximum volume percent and ending with the word "methanol." (Example: M85 Methanol)."</p>
(9) Section 3.13. Oil	Delete section 3.13.
(10) Section 3.14. Automatic Transmission Fluid	Delete section 3.14.
(11) Section 3.15.2. Labeling of Retail Dispensers	<p>Add a new subsection which reads: "3.15.2.5. Labeling of Retail Dispensers Containing Not More Than 5% Biodiesel. Each retail dispenser of biodiesel blend containing not more than five percent biodiesel must be labeled "May contain up to 5% Biodiesel.""</p> <p>Add a new subsection which reads: "3.15.2.6. Labeling of Retail Dispensers Containing More Than 5% Biodiesel. Each retail dispenser of biodiesel or biodiesel blend containing more than five percent biodiesel must be labeled with the capital letter B followed by the numerical value representing the volume percentage of biodiesel fuel and ending with either</p>

Modified Section:	Modification:
	"biodiesel" or "biodiesel blend" (examples: B100 Biodiesel; B60 Biodiesel blend)."
(12) Section 3.15.4. Exemption	Delete section 3.15.4.

[Statutory Authority: RCW 19.94.190, 19.112.020, 19.112.140 and chapter 34.05 RCW. WSR 13-03-054, § 16-662-115, filed 1/11/13, effective 2/11/13; WSR 12-08-041, § 16-662-115, filed 3/30/12, effective 4/30/12. Statutory Authority: Chapters 19.94, 19.112, 34.05 RCW, and 2010 c 96. WSR 10-18-088, § 16-662-115, filed 9/1/10, effective 10/2/10. Statutory Authority: Chapters 19.94, 19.112, and 34.05 RCW. WSR 09-19-007, § 16-662-115, filed 9/3/09, effective 10/4/09. Statutory Authority: Chapters 19.112 and 34.05 RCW. WSR 07-05-083, § 16-662-115, filed 2/21/07, effective 3/24/07. Statutory Authority: Chapters 19.94 and 34.05 RCW. WSR 05-10-088, § 16-662-115, filed 5/4/05, effective 6/4/05; WSR 03-08-017, § 16-662-115, filed 3/25/03, effective 4/25/03. Statutory Authority: RCW 19.94.195. WSR 98-13-072, § 16-662-115, filed 6/15/98, effective 7/16/98. Statutory Authority: Chapter 19.94 RCW. WSR 97-12-075, § 16-662-115, filed 6/4/97, effective 7/5/97.]

**WAC 16-662-120 Inspections of the net contents of packaged goods under NIST Handbook 133.** WSDA inspects packages using either used dry tare or unused dry tare in accordance with the procedures outlined in *NIST Handbook 133*.

[Statutory Authority: Chapters 19.94, 19.112, and 34.05 RCW. WSR 12-02-021, § 16-662-120, filed 12/28/11, effective 1/28/12. Statutory Authority: Chapters 19.94 and 34.05 RCW. WSR 05-10-088, § 16-662-120, filed 5/4/05, effective 6/4/05.]

**WAC 16-662-125 Enforcement actions for price verification inspections under NIST Handbook 130.** WSDA uses *NIST Handbook 130*, Examination Procedure For Price Verification, Section 11.2., Model Enforcement Levels. Overcharges will be used to determine price accuracy for enforcement actions under chapter 19.94 RCW.

[Statutory Authority: RCW 19.94.190, 19.112.020, 19.112.140, and chapter 34.05 RCW. WSR 12-08-041, § 16-662-125, filed 3/30/12, effective 4/30/12. Statutory Authority: Chapters 19.94 and 34.05 RCW. WSR 05-10-088, § 16-662-125, filed 5/4/05, effective 6/4/05.]

**WAC 16-662-140 Retail sales of motor fuels.** All devices used for retail motor fuel sales shall:

- (1) Display the price per gallon or price per liter as set forth in *NIST Handbook 44* adopted under this chapter;
- (2) Indicate the amount of fuel delivered during a single retail transaction as set forth in *NIST Handbook 44* adopted under this chapter;
- (3) Compute and display the selling price per unit as set forth in *NIST Handbook 44* adopted under this chapter;
- (4) Compute and display the total selling price for a single retail transaction as set forth in *NIST Handbook 44* adopted under this chapter; and
- (5) Provide a receipt for retail transactions as set forth in *NIST Handbook 44* adopted under this chapter.

[Statutory Authority: RCW 19.94.190, 19.112.020, 19.112.140 and chapter 34.05 RCW. WSR 13-03-054, § 16-662-140, filed 1/11/13, effective 2/11/13.]

**WAC 16-662-145 Posting of motor fuel prices—Cash and credit sales.** The following rules apply to the posting of prices of retail sales of motor fuels. As used herein, motor

fuel means any fuel used in motor vehicles including, but not limited to, gasoline, diesel, propane, and alcohol-gasoline blends. As used herein, motor vehicles shall include all wheeled motorized vehicles, and all boats and airplanes.

(1) The posted or advertised price of motor fuel at retail outlets must be available to all consumers. The grade of fuel and any condition or qualification required to obtain the posted price must be clearly displayed in letters of contrasting color at least one-half the size of the posted price and immediately adjacent thereto.

(2) A cash price may be posted or advertised if the posting of the price clearly shows it to be limited to cash purchases. The information shall be in letters at least one-half the size of the posted price and immediately adjacent thereto.

(3) Cash and credit sales. If a retailer elects to establish separate islands or individual dispensers for cash and credit sales, the islands or dispensers shall be clearly marked as such in letters at least six inches in height and of proportional width.

(4) Posted prices of motor fuels at retail outlets shall include all federal, state, and local taxes.

[Statutory Authority: RCW 19.94.190, 19.112.020, 19.112.140 and chapter 34.05 RCW. WSR 13-03-054, § 16-662-145, filed 1/11/13, effective 2/11/13.]